

View Online at <https://aerobasegroup.com/nsn/5930-01-205-3256>

**Thread Class:**

3a single pressure connection

**Overall Length:**

3.000 inches

**Outside Diameter:**

0.438 inches single connection

**Overall Diameter:**

1.000 inches

**Pressure Switch Type:**

Absolute

**Mounting Method:**

Input port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4000.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

7000.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage and 1.0 amperes lamp load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

25.00 actuation point pounds per square inch absolute and 15.00 deactuation point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Swivel nut, flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0