

View Online at <https://aerobasegroup.com/nsn/5930-01-205-3256>

Thread Class:

3a single pressure connection

Overall Length:

3.000 inches

Outside Diameter:

0.438 inches single connection

Overall Diameter:

1.000 inches

Pressure Switch Type:

Absolute

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

4000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7000.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage and 1.0 amperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

25.00 actuation point pounds per square inch absolute and 15.00 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel nut, flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0