

View Online at <https://aerobasegroup.com/nsn/5930-01-205-3584>

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and watertight and salt spray resistant

Overall Length:

4.350 inches

Overall Diameter:

5.688 inches

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

28003

Knob Manufacturer Part Number:

8316-01

Operating Temperature Range:

-62.0/+75.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section rear

Mounting Facility Circle Radius:

2.812 inches single mounting facility

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate and metallic inclosure

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Switch is in a enclosed cylinder with 3 drain holes

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0