Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-205-6981

| Overall Length: |
|---|
| 1.760 inches |
| Overall Height: |
| 1.570 inches |
| Overall Width: |
| 1.150 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.110 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.590 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 0.900 inches single mounting facility |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Actuator Type: |
| Lever all actuators |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 10 all actuators |
| Terminal Type: |
| Printed circuit |
| Contact Switching Action: |
| Breaks before makes each section in-line |
| Contact Load Current Rating: |
| 50.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section |
| Contact Arrangement Truth Table: |
| Bcd with complement, 2 pole - 10 positions each section |
| Color: |
| White each indicator marking |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Style Designator: |
| |

Rectangular inline indicating

Code Indicating Wheel Switch - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A052b0