## NSN 5930-01-205-7383

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-205-7383

## **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Fungus resistant and shock resistant and vibration resistant

#### **Overall Length:**

1.154 inches

#### **Overall Height:**

2.720 inches

#### **Overall Width:**

0.904 inches

#### **Body Width:**

0.870 inches

#### **Body Height:**

2.440 inches

#### Case Material:

Metal

## Actuator Length:

0.891 inches

## Actuator Style:

Rectangular

#### Actuator Height:

0.070 inches

## Actuator Width:

0.668 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

Advance single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000

amperes inductive ac and 750.000 milliamperes lamp ac

### **Special Features:**

0.290 in. High spacer

# NSN 5930-01-205-7383

Push Switch - Page 2 of 2



## Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0