NSN 5930-01-205-7384

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-205-7384

Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Fungus resistant and shock resistant and vibration resistant					
Overall Length:					
1.154 inches					
Overall Height:					
2.720 inches					
Overall Width:					
0.904 inches					
Body Width:					
0.870 inches					
Body Height:					
2.440 inches					
Case Material:					
Metal					
Actuator Length:					
0.891 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.070 inches					
Actuator Width:					
0.668 inches					
Actuator Color:					
White single actuator					
Illuminated Actuator Color:					
Green single actuator and white single actuator					
Actuator Inscription:					
Vcfar on low sens baseline single actuator					
Illuminated Actuator Color Sequence:					
Upper left and right half of actuator white lower half of actuator green					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Nonpile-up Contact Arrangement:					

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-205-7384

Push Switch - Page 2 of 2



Termina	I Type	And (Quantit	٧.
	11 1 1 1 1 1 1	Allu '	wuanni	ν.

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0