

View Online at <https://aerobasegroup.com/nsn/5930-01-205-7385>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Fungus resistant and shock resistant and vibration resistant

**Overall Length:**

1.154 inches

**Overall Height:**

2.720 inches

**Overall Width:**

0.904 inches

**Body Width:**

0.870 inches

**Body Height:**

2.440 inches

**Case Material:**

Metal

**Actuator Length:**

0.891 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.070 inches

**Actuator Width:**

0.668 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator and white single actuator

**Actuator Inscription:**

Fill pulse movch mapon baseline single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator white lower half of actuator green

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

**Special Features:**

0.290 in. High spacer

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0