

View Online at <https://aerobasegroup.com/nsn/5930-01-206-0529>

Body Style:

Hole mounted

Overall Length:

0.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.250 inches

Overall Height:

0.885 inches

Overall Width:

0.345 inches

Body Length:

0.750 inches

Body Width:

0.345 inches

Body Height:

0.578 inches

Unthreaded Mounting Hole Diameter:

0.089 inches

Actuator Length:

0.438 inches

Actuator Style:

Leaf

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.542 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

2350-01-089-1261 gun, air defense

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

26.0 ounces

Actuator Movement:

Between 0.032 pretravel inches and 0.006 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-s-8805/46 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0