NSN 5930-01-206-0534

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-206-0534

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Fungus resistant and shock resistant and vibration resistant
Overall Length:
1.154 inches
Overall Height:
2.720 inches
Overall Width:
0.904 inches
Body Width:
0.870 inches
Body Height:
2.440 inches
Case Material:
Metal
Actuator Length:
0.891 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.668 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
On off single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator white lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-206-0534

Push Switch - Page 2 of 2



Special	Features:
---------	-----------

0.290 in. High spacer horizontal split lens

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0