## NSN 5930-01-206-1212

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-206-1212

Hazardous Locations/environmental Protection:

Vibration resistant

**Overall Length:** 

0.344 inches

## **Overall Height:**

0.080 inches

## **Body Diameter:**

0.263 inches

## Tempurature Sensing Element Type:

Internal sensor

## Mounting Method:

Clamp

#### **Contact Action Stimulus:**

Increase

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

## Terminal Type:

Wire lead

### **Contact Load Current Rating:**

1.0 amperes resistive load first voltage

#### Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

#### **Contact Stimulus Rating:**

195.00 actuation point degrees fahrenheit and 165.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

#### **Frequency In Hertz:**

60.0 first voltage

Media For Which Designed:

Gas

## Style Designator:

Disc

## Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-s-24236/13 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

# NSN 5930-01-206-1212

Thermostatic Switch - Page 2 of 2

**Fiig:** A048b0

