NSN 5930-01-206-1215

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-206-1215

| Body Style: |
|---|
| Bushing mounted |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.498 inches |
| Overall Width: |
| 0.260 inches |
| Bushing Length: |
| 0.344 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.260 inches |
| Body Height: |
| 0.639 inches |
| Case Material: |
| Plastic |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.375 inches |
| Actuator Height: |
| 0.359 inches |
| Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 6.000 amperes resistive dc and 3.000 amperes resistive ac |

Precious Material And Location:

Contacts and terminal surfaces silver

NSN 5930-01-206-1215Push Switch - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0