## NSN 5930-01-206-1219

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-206-1219

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Fungus proof and shock resistant and vibration resistant
Overall Length:
1.154 inches
Overall Height:
2.720 inches
Overall Width:
0.904 inches
Body Width:
0.870 inches
Body Height:
2.440 inches
Case Material:
Metal
Actuator Length:
0.891 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.668 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and white single actuator
Actuator Inscription:
Long range anti chaff single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator green lower half of actuator white
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonnile-un Contact Arrangement:

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

## NSN 5930-01-206-1219

Push Switch - Page 2 of 2



S	pe	cia	l F	ea	tui	es
---	----	-----	-----	----	-----	----

0.290 in. High spacer horizontal split lens

**Terminal Type And Quantity:** 

11 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0