

View Online at <https://aerobasegroup.com/nsn/5930-01-206-2221>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

0.688 inches

**Body Height:**

2.446 inches

**Actuator Length:**

0.750 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.205 inches and 0.225 inches

**Actuator Width:**

0.620 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Helicopter, sh-60f, sh-60b

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, permanent internal jumpers, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0