

View Online at <https://aerobasegroup.com/nsn/5930-01-206-4385>

**Thread Class:**

2b all pressure connection

**Hazardous Locations/environmental Protection:**

Watertight and dustproof

**Overall Length:**

6.844 inches

**Overall Height:**

2.688 inches

**Overall Width:**

5.812 inches

**Body Length:**

2.750 inches

**Body Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Mounting Facility Centers:**

5.250 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.438 inches all pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+7.00/+70.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0