

View Online at <https://aerobasegroup.com/nsn/5930-01-206-5555>

Thread Class:

2b single pressure connection

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dusttight and oiltight

Overall Length:

2.810 inches

Overall Height:

5.750 inches

Overall Width:

2.320 inches

Body Height:

3.370 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Tamper proof cap and electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

7.5 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+30.00/+200.00 actuation point pounds per square inch gage and +20.00/+170.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw with scale and internal deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0