NSN 5930-01-206-6310

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-206-6310

| g |
|---|
| Body Style: |
| Hole mount |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.812 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| 0.969 inches |
| Body Height: |
| 1.625 inches |
| Switch Actuator Quantity: |
| 1 |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.625 inches |
| Actuator Height: |
| 0.750 inches |
| Actuator Position-action Relationship: |
| Down position maintained and up position maintained |
| Actuator Position-locking Relationship: |
| Down position locked in |
| Actuator Inscription: |
| Crew-fire extinguisher single actuator |
| Maximum Voltage Rating In Volts: |
| 24.0 dc |
| End Application: |
| 2350-01-115-1579 |
| Mounting Surface To Terminal End Distance: |
| 1.781 inches |
| Inclosure Type: |
| Uninclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained 1st switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc |
| Special Features: |
| Mounted on bracket 11653306 with cord 11594330 |
| Precious Material And Location: |
| Terminals silver |
| Terminal Type And Quantity: |

2 pin

NSN 5930-01-206-6310

Toggle Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0