NSN 5930-01-207-0020

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-207-0020

| Body Style: |
|--|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Waterproof |
| Body Width: |
| 0.740 inches |
| Body Height: |
| 0.990 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.300 inches |
| Actuator Width: |
| 0.990 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 2.660 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal and rfi shielding |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac |
| Precious Material And Location: |
| Terminal surfaces gold |
| Test Data Document: |
| 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

17 pin

NSN 5930-01-207-0020

Push Switch - Page 2 of 2



| Spec | ifica | ation | Data: |
|------|-------|-------|-------|
|------|-------|-------|-------|

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0