## NSN 5930-01-207-0024

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5930-01-207-0024
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Waterproof
Body Length:
1.200 inches
Body Width:
1.200 inches
Body Height:
3.150 inches
Case Material:
Metal
Actuator Color:
Yellow single actuator
Illuminated Actuator Color:
Yellow single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Gun fire control system, mk 68
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac
Precious Material And Location:
Terminal surfaces gold
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
17 pin
Specification Data:
81349-mil-22885/80 government specification
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5930-01-207-0024

Push Switch - Page 2 of 2



Demi			

No

Fiig:

A053a0