NSN 5930-01-207-2446

Slide Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-207-2446

Body Style:
Hole mounted
Overall Length:
1.656 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.406 inches
Overall Height:
0.984 inches
Overall Width:
0.531 inches
Body Width:
0.531 inches
Body Height:
0.328 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.141 inches
Actuator Length:
0.281 inches
Actuator Height:
0.344 inches
Actuator Width:
0.219 inches
Actuator Position-action Relationship:
Up position maintained and down position momentary and center position maintained
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary, two positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 6.000 amperes resistive ac
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:

NSN 5930-01-207-2446

Slide Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0