

View Online at <https://aerobasegroup.com/nsn/5930-01-207-3451>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

11.9 millimeters

**Body Length:**

34.0 millimeters

**Body Width:**

23.1 millimeters

**Actuator Style:**

Round

**Actuator Diameter:**

9.4 millimeters

**Actuator Height:**

25.4 millimeters

**Actuator Position-action Relationship:**

Center position maintained and left position maintained and right position momentary

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

34.8 millimeters

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes inductive dc and 18.000 amperes resistive dc

**Special Features:**

Ecase - material plastic, length 34.0 millimeters, width 23.1 millimeters, height 72.1 millimeters; end use caterpillar 3304 generator set onboard 110 ft wpb coast guard vessels

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0