## NSN 5930-01-207-6502

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-207-6502

**Overall Length:** 2.500 inches **Outside Diameter:** 0.125 inches single connection **Overall Diameter:** 1.190 inches **End Application:** 5985-01-129-1794 mast group hydr **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -54.0 degrees celsius and 107.0 degrees celsius **Mounting Method:** Inlet connection Thready Qty Per Inch (tpi): 27 single pressure connection **Contact Action Stimulus:** Decrease **Proof Pressure:** 75.00 pounds per square inch gage **Thread Size:** 0.125 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Tab w/screw **Contact Load Current Rating:** 5.0 amperes resistive load and 3.0 amperes inductive load single voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Range:** +2.00 to 48.00 actuation point pounds per square inch gage and +3.00 to 50.00 deactuation point pounds per square inch gage **Contact Adjustment Type:** External actuation point screw **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage **Pressure Connector Type:** Flared, threaded external single connection Media For Which Designed:

Gas or liquid

**Style Designator:** 

Cylindrical

## NSN 5930-01-207-6502

Pressure Switch - Page 2 of 2



T	'nr	ead	<b>Series</b>	Design	nator:

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0