

View Online at <https://aerobasegroup.com/nsn/5930-01-207-6505>

**Body Style:**

Bushing mount

**Bushing Length:**

0.500 inches

**Body Length:**

1.300 inches

**Body Width:**

0.930 inches

**Body Height:**

1.150 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.650 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

4920-01-038-0984

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

6 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

18 turret

**Specification Data:**

81349-mil-s-8805/93 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0