## NSN 5930-01-207-6506

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-207-6506

## **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Corrosion resistant

## **Overall Length:**

4.000 inches

#### **Overall Height:**

2.500 inches

#### **Overall Width:**

1.562 inches

#### Actuator Style:

Round

## **Actuator Free Position Height:**

1.500 inches

#### Housing Length:

4.000 inches

## Housing Width:

1.562 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

## Maximum Voltage Rating In Volts:

115.0 dc

#### **End Application:**

5985-01-129-1794 mast group hydr

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

4.0 inch-ounces

#### Switch Actuating Force:

80.0 inch-ounces

## Contact Load Current Rating At Maximum Rated Voltage:

1.100 amperes resistive dc

#### **Terminal Type And Quantity:**

3 screw

#### Shelf Life:

N/a

# NSN 5930-01-207-6506

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

