NSN 5930-01-207-6507

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-207-6507

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
4.000 inches
Overall Height:
2.500 inches
Overall Width:
1.562 inches
Actuator Style:
Round
Actuator Free Position Height:
1.500 inches
Housing Length:
4.000 inches
Housing Width:
1.562 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
4.450 inches
1.156 inches
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 115.0 dc
Maximum Voltage Rating In Volts: 115.0 dc End Application:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 inch-ounces
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 inch-ounces Switch Actuating Force:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 inch-ounces Switch Actuating Force: 80.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage:
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 inch-ounces Switch Actuating Force: 80.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.100 amperes resistive dc
Maximum Voltage Rating In Volts: 115.0 dc End Application: 5985-01-129-1794 mast group hydr Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 inch-ounces Switch Actuating Force: 80.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage:

N/a

NSN 5930-01-207-6507

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A053a0