NSN 5930-01-207-7891

Sensitive Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-207-7691
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
6.932 inches
Overall Width:
1.594 inches
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
1.782 inches
Housing Length:
5.062 inches
Housing Width:
1.594 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.5 inch-ounces
Switch Actuating Force:
48.0 inch-ounces
Actuator Movement:
10.0 pretravel degrees
Contact Load Current Rating At Maximum Rated Voltage:
1.200 amperes resistive ac
Terminal Type And Quantity:

3 screw

NSN 5930-01-207-7891

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0