NSN 5930-01-207-9116

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-207-9116
Overall Length:
3.025 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.288 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 ac at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
20.0 amperes resistive load ac at sea level
Precious Material And Location:
Contact and terminal surfaces silver
Precious Material:
Silver
Style Designator:

Tap, circuit selector

NSN 5930-01-207-9116

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0