NSN 5930-01-208-1233

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-208-1233

Body Style:	
Panel mount	
Hazardous Locations/environmental Protection:	
Fungus resistant and shock resistant and vibration resistant	
Overall Length:	
1.154 inches	
Overall Height:	
2.720 inches	
Overall Width:	
0.904 inches	
Body Width:	
0.870 inches	
Body Height:	
2.440 inches	
Case Material:	
Metal	
Actuator Length:	
0.891 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.070 inches	
Actuator Width:	
0.668 inches	
Actuator Color:	
White single actuator and white single actuator	
Illuminated Actuator Color:	
Green single actuator and yellow single actuator	
Actuator Inscription:	
Rotation on rotation off single actuator	
Illuminated Actuator Color Sequence:	
Upper half of actuator green lower half of actuator yellow	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Nonpile-up Contact Arrangement:	
2 pole, double throw, one position momentary single switch unit	
Contact Load Current Rating At Maximum Rated Voltage:	

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-208-1233

Push Switch - Page 2 of 2



Special	Features:
---------	-----------

0.290 in. High spacer horizontal split lens

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0