

View Online at <https://aerobasegroup.com/nsn/5930-01-208-2274>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.256 inches 1st mounting facility

**Overall Length:**

2.050 inches

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Nonturn Device Type:**

Slotted bushing at 12: 00 o'clock

**Operating Temperature Range:**

-20.0/+80.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing 1st mounting facility

**Features Provided:**

Cam actuated

**Thready Qty Per Inch (tpi):**

40 1st mounting facility

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contacts and terminals gold

**Precious Material:**

Gold

**Thread Series Designator:**

Uns 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0