## NSN 5930-01-208-2274

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-208-2274

**Thread Class:** 

2a 1st mounting facility

Thread Length:

0.256 inches 1st mounting facility

**Overall Length:** 

2.050 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.500 inches single actuator

**Nonturn Device Type:** 

Slotted bushing at 12: 00 o'clock

**Operating Tempurature Range:** 

-20.0/+80.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing 1st mounting facility

**Features Provided:** 

Cam actuated

Thready Qty Per Inch (tpi):

40 1st mounting facility

**Thread Size:** 

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

10 single actuator

**Shaft Type:** 

Round, slotted single actuator

**Terminal Type:** 

Printed circuit

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

125.0 milliamperes resistive load dc at sea level

**Precious Material And Location:** 

Contacts and terminals gold

**Precious Material:** 

Gold

**Thread Series Designator:** 

Uns 1st mounting facility

## NSN 5930-01-208-2274

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0