

View Online at <https://aerobasegroup.com/nsn/5930-01-208-3583>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and driptight

**Body Length:**

0.960 inches

**Body Width:**

0.960 inches

**Body Height:**

1.910 inches

**Actuator Length:**

0.510 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.510 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Green single actuator and yellow single actuator

**Actuator Inscription:**

Gmts/uut single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Emi shielding

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0