## NSN 5930-01-208-7713

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-208-7713

**Inside Diameter:** 0.250 inches single connection **Hazardous Locations/environmental Protection:** Waterproof **Overall Length: 4.750** inches **Overall Diameter:** 2.230 inches **End Application:** 2350-01-031-0586 howitzer medium **Pressure Switch Type:** Gage Width Across Flats: 0.880 inches **Mounting Method:** Clamp Thready Qty Per Inch (tpi): 18 single pressure connection **Contact Action Stimulus:** Increase **Thread Size:** 0.250 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Connector, receptacle **Contact Adjustability:** Actuation point not adjustable **Contact Stimulus Rating:** 4.00 actuation point pounds per square inch and 8.00 actuation point pounds per square inch **Contact Voltage Rating In Volts:** 24.0 dc at sea level single voltage **Pressure Connector Type:** Double compression, threaded internal single connection Media For Which Designed: Gas or liquid **Style Designator:** Cylindrical **Test Data Document:** 

81349-mil-s-12211 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Nptf single pressure connection

## NSN 5930-01-208-7713

Pressure Switch - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

96906-ms90530 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0