NSN 5930-01-209-1658

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-209-1658

Overall Length:
0.971 inches
Overall Height:
0.562 inches
Overall Width:
0.300 inches
Body Diameter:
0.450 inches
Body Length:
0.660 inches
Unthreaded Mounting Hole Diameter:
Between 0.108 inches and 0.122 inches
Distance Between Mounting Facility Centers:
0.567 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Contact Action Stimulus:
Decrease
Decrease
Decrease Mounting Facility Pattern:
Decrease Mounting Facility Pattern: Two position in-line
Decrease Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement:
Decrease Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
Decrease Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating: -0.50 deactuation point inches of vacuum
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating: -0.50 deactuation point inches of vacuum Contact Voltage Rating In Volts:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating: -0.50 deactuation point inches of vacuum Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating: -0.50 deactuation point inches of vacuum Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Frequency In Hertz:
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.5 amperes inductive load second voltage and 1.1 amperes inductive load second voltage Contact Adjustability: Deactuation point not adjustable Contact Stimulus Rating: -0.50 deactuation point inches of vacuum Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage

Cylindrical w/flange

NSN 5930-01-209-1658

Thermostatic Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0