# NSN 5930-01-209-1844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-209-1844

# **Overall Length:**

0.850 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

# **Overall Height:**

0.906 inches

# **Overall Width:**

0.320 inches

#### **Body Length:**

0.850 inches

### **Body Width:**

0.320 inches

#### Body Height:

0.660 inches

#### **Case Material:**

Metal

# Unthreaded Mounting Hole Diameter:

0.117 inches

# Actuator Style:

Round

# Actuator Diameter:

0.109 inches

#### Actuator Height:

0.350 inches

# **Actuator Free Position Height:**

0.395 inches

# Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

# Inclosure Type:

Fully enclosed

# Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

#### Switch Release Force:

0.8 ounces

#### Switch Actuating Force:

12.0 ounces

#### **Actuator Movement:**

Between 0.045 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac

# Terminal Type And Quantity:

4 quick disconnect, male

# NSN 5930-01-209-1844

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

