NSN 5930-01-209-2247

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-209-2247

| view Online at https://aerobasegroup.com/nsn/5930-01-209-2247 |
|---|
| Thread Class: |
| 2a single pressure connection |
| Overall Length: |
| 3.238 inches |
| Outside Diameter: |
| 0.250 inches single connection |
| Body Length: |
| 2.688 inches |
| Overall Diameter: |
| 1.250 inches |
| Pressure Switch Type: |
| Gage |
| Width Across Flats: |
| 1.000 inches |
| Operating Tempurature Rating: |
| Between -20.0 degrees fahrenheit and 165.0 degrees fahrenheit |
| Mounting Method: |
| Clamp |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 4500.00 pounds per square inch gage |
| Thread Size: |
| 0.438 inches single pressure connection |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Sensing Element Burst Pressure: |
| 7500.00 pounds per square inch gage |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 2.0 amperes inductive load single voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 1275.00 actuation point pounds per square inch gage and 1200.00 deactuation point pounds per square inch gage |
| Contact Voltage Rating In Volts: |
| 115.0 ac at sea level single voltage |
| Pressure Connector Type: |

Special Features:

Altered iaw navy dwg no.2816042

Flared, threaded external single connection

NSN 5930-01-209-2247

Pressure Switch - Page 2 of 2



| Frequency In Hertz: |
|--------------------------------|
| 60.0 single voltage |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Cylindrical |
| Thread Series Designator: |
| Unf single pressure connection |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A048b0