NSN 5930-01-209-9523

Pressure Switch - Page 1 of 2

Inside Diameter:



View Online at https://aerobasegroup.com/nsn/5930-01-209-9523

| 0.125 inches single connection | | | | |
|--|--|--|--|--|
| Overall Length: | | | | |
| 3.250 inches | | | | |
| Overall Height: | | | | |
| 0.969 inches | | | | |
| Overall Width: | | | | |
| 1.938 inches | | | | |
| Body Length: | | | | |
| 3.125 inches | | | | |
| End Application: | | | | |
| Radar set an/tps-63 | | | | |
| Pressure Switch Type: | | | | |
| Gage | | | | |
| Mounting Method: | | | | |
| Input port | | | | |
| Thready Qty Per Inch (tpi): | | | | |
| 27 single pressure connection | | | | |
| Contact Action Stimulus: | | | | |
| Increase | | | | |
| Proof Pressure: | | | | |
| 90.00 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.125 inches single pressure connection | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 1 pole, double throw, one position momentary | | | | |
| Terminal Type: | | | | |
| Screw | | | | |
| Contact Load Current Rating: | | | | |
| 15.0 amperes resistive load single voltage | | | | |
| Contact Adjustability: | | | | |
| Actuation point adjustable | | | | |
| Contact Adjustment Type: | | | | |
| External actuation point serrated nut | | | | |
| Contact Voltage Rating In Volts: | | | | |
| 250.0 ac at sea level single voltage | | | | |
| Pressure Connector Type: | | | | |
| Plain, threaded internal single connection | | | | |
| Media For Which Designed: | | | | |
| Gas or liquid | | | | |
| Style Designator: | | | | |
| Cylindrical w/flange | | | | |

NSN 5930-01-209-9523

Pressure Switch - Page 2 of 2



| Ī | hread | Series | Desig | nator: |
|---|-------|---------------|-------|--------|
| | | | | |

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0