NSN 5930-01-210-5268

Pressure Switch - Page 1 of 2

Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-210-5268

2.875 inches
Overall Width:
4.938 inches
Body Length:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
216.00 pounds per square inch gage
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load third voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+10.00 to 180.00 actuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level fourth voltage
Special Features:
No resistor, 0.438 in, 20 thread clean out

NSN 5930-01-210-5268 Pressure Switch - Page 2 of 2



Frequency in Hertz:
60.0 second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0