# NSN 5930-01-210-5367

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-210-5367

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Dustproof

### **Overall Length:**

0.960 inches

#### **Overall Height:**

2.360 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

0.688 inches

#### **Body Width:**

0.688 inches

#### **Body Height:**

1.910 inches

# Case Material:

Metal

#### ivietai

Actuator Length:

#### 0.960 inches

**Actuator Style:** 

#### Rectangular

**Actuator Height:** 

#### 0.450 inches

Actuator Width:

0.960 inches

#### Actuator Color:

Green single actuator and yellow single actuator

#### Illuminated Actuator Color:

Green single actuator and yellow single actuator

#### **Actuator Inscription:**

Action, run single actuator

#### **Illuminated Actuator Color Sequence:**

Upper half of actuator green, lower half of actuator yellow

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-210-5367

Push Switch - Page 2 of 2



### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

# Special Features:

Emi shielding

Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

5 tab, solder lug and 6 turret

### Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A053a0