

View Online at <https://aerobasegroup.com/nsn/5930-01-210-6382>

**Overall Length:**

8.687 inches

**Overall Height:**

4.500 inches

**Overall Width:**

4.500 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and cam actuated

**Contact Voltage Rating In Volts:**

600.0 highest dc voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Cam Actuated Switch Contact Arrangement:**

2 pole, single throw, both positions maintained each switch each section periphery

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

6.0 amperes resistive load lowest dc voltage rating at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0