

View Online at <https://aerobasegroup.com/nsn/5930-01-210-6382>

Overall Length:

8.687 inches

Overall Height:

4.500 inches

Overall Width:

4.500 inches

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and cam actuated

Contact Voltage Rating In Volts:

600.0 highest dc voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Cam Actuated Switch Contact Arrangement:

2 pole, single throw, both positions maintained each switch each section periphery

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

6.0 amperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0