NSN 5930-01-210-7105

Lever Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-210-7105

| Hazardous Locations/environmental Protection: |
|---|
| Dustproof |
| Overall Length: |
| 6.500 inches |
| Overall Height: |
| 5.500 inches |
| Overall Width: |
| 3.500 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Maximum Voltage Rating In Volts: |
| 120.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| |
| Nonpile-up Contact Arrangement: |
| Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit |
| - |
| 1 pole, single throw, both positions maintained single switch unit |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a Unit Of Measure: |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a Unit Of Measure: Demilitarization: |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| 1 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 20.000 amperes resistive ac Special Features: Two electrical access ports legend plate reads on off Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: |