

View Online at <https://aerobasegroup.com/nsn/5930-01-210-7131>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and oiltight

Actuator Style:

Round

Actuator Diameter:

0.490 inches

Actuator Height:

0.625 inches

Actuator Free Position Height:

0.500 inches

Housing Height:

2.600 inches

Housing Length:

7.060 inches

Housing Width:

3.312 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.812 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

320.0 inch-ounces

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0