## NSN 5930-01-210-7211

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-210-7211

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and dustproof and driptight
Overall Length:
6.375 inches
Overall Height:
2.438 inches
Overall Width:
2.312 inches
Case Material:
Metal
Actuator Length:
1.875 inches
Actuator Style:
Roller arm
Actuator Height:
0.844 inches
Actuator Roller Diameter:
1.375 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.438 inches
Housing Length:
5.094 inches
Housing Width:
2.312 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.328 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.750 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
160.0 inch-ounces

## **Actuator Movement:**

14.0 pretravel degrees and 88.0 overtravel degrees and 12.0 differential degrees

## NSN 5930-01-210-7211

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 25.000 amperes resistive ac and 25.000 amperes inductive ac

**Terminal Type And Quantity:** 

4 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0