NSN 5930-01-211-4203

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-211-4203
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.625 inches
Overall Height:
3.750 inches
Overall Width:
3.250 inches
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
1.641 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.641 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Throw Quantity:
4 each section periphery
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
120.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Threaded stud
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level

Thread Series Designator:

Unc single mounting facility

NSN 5930-01-211-4203

Rotary Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0