## NSN 5930-01-211-6363

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-211-6363

view Online at https://aerobasegroup.com/hsh/0000-01-211-0000
Body Style:
Hole mounted
Overall Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.880 inches
Overall Height:
1.094 inches
Overall Width:
0.406 inches
Body Length:
1.090 inches
Body Width:
0.400 inches
Body Height:
0.630 inches
Unthreaded Mounting Hole Diameter:
0.110 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.410 inches
Actuator Style:
Leaf
Actuator Width:
0.170 inches
Actuator Free Position Height:
0.140 inches
Maximum Voltage Rating In Volts:
277.0 ac and 250.0 dc
End Application:
4210-01-137-9944 truck, fire, crash a/s32p-19 bumper turret assembly
Inclosure Type:
Fully enclosed

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

#### **Switch Release Force:**

2.0 ounces

#### **Switch Actuating Force:**

9.0 ounces

### **Actuator Movement:**

Between 0.060 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

#### **Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 11.000 amperes resistive ac

# NSN 5930-01-211-6363

Sensitive Switch - Page 2 of 2



Contacts silver
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:

**Precious Material And Location:** 

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0