NSN 5930-01-211-6363

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-211-6363

Body Style:

Hole mounted

Overall Length:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.880 inches

Overall Height:

1.094 inches

Overall Width:

0.406 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.630 inches

Unthreaded Mounting Hole Diameter:

0.110 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Actuator Style:

Leaf

Actuator Width:

0.170 inches

Actuator Free Position Height:

0.140 inches

Maximum Voltage Rating In Volts:

277.0 ac and 250.0 dc

End Application:

4210-01-137-9944 truck, fire, crash a/s32p-19 bumper turret assembly

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

9.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 11.000 amperes resistive ac

NSN 5930-01-211-6363

Sensitive Switch - Page 2 of 2



Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0