NSN 5930-01-211-6365

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style: Panel mount

Dustproof

Overall Length: 1.210 inches Overall Height: 3.320 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-211-6365

Between 0.950 inches and 0.970 inches
Body Length:
1.200 inches
Body Width:
Between 0.950 inches and 0.970 inches
Body Height:
3.110 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.050 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.720 inches and 0.750 inches
Actuator Color:
White single actuator and white single actuator and white single actuator
Illuminated Actuator Color:
Yellow single actuator and yellow single actuator and white single actuator
Actuator Inscription:
Release/vrfy/vrfy single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator white lower left half of actuator yellow lower right half of actuator yellow
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

NSN 5930-01-211-6365

Push Switch - Page 2 of 2



Special Features:
Three-way split lens
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
12 turret and 8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0