

View Online at <https://aerobasegroup.com/nsn/5930-01-211-6365>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.210 inches

Overall Height:

3.320 inches

Overall Width:

Between 0.950 inches and 0.970 inches

Body Length:

1.200 inches

Body Width:

Between 0.950 inches and 0.970 inches

Body Height:

3.110 inches

Case Material:

Metal

Actuator Length:

Between 1.020 inches and 1.050 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.164 inches and 0.210 inches

Actuator Width:

Between 0.720 inches and 0.750 inches

Actuator Color:

White single actuator and white single actuator and white single actuator

Illuminated Actuator Color:

Yellow single actuator and yellow single actuator and white single actuator

Actuator Inscription:

Release/vrfy/vrfy single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator white lower left half of actuator yellow lower right half of actuator yellow

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Three-way split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0