NSN 5930-01-211-6432

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mount

Overall Length: 0.750 inches



View Online at https://aerobasegroup.com/nsn/5930-01-211-6432

Corrosion resistant and fungus resistant and moisture resistant

Overall Height:				
2.320 inches				
Overall Width:				
0.750 inches				
Body Length:				
0.688 inches				
Body Width:				
0.688 inches				
Body Height:				
2.240 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.080 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
White single actuator				
Illuminated Actuator Color:				
Green single actuator				
Actuator Inscription:				
Ecs single actuator				
Maximum Voltage Rating In Volts:				
28.0 dc				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Nonpile-up Contact Arrangement:				
2 pole, double throw, one position momentary single switch unit				
Contact Load Current Rating At Maximum Rated Voltage:				
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc				

NSN 5930-01-211-6432

Push Switch - Page 2 of 2



Draai	aua N	latari:	1 A n d	Location:
rieci	ous IV	าสเษาเ	ai Aiiu	Location.

Contacts silver and contact surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0