

View Online at <https://aerobasegroup.com/nsn/5930-01-211-6656>

**Thread Class:**

2b 1st mounting facility

**Overall Length:**

6.469 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Individual Section Quantity:**

9

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

8164-12ey

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

0.906 inches 2nd mounting facility

**Mounting Method:**

Threaded stud 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.190 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Special Features:**

Item must comply with requirements of desc production standard no. L03443; for navy nuclear propulsion plant products only

**Precious Material And Location:**

Contacts and rotor contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0