NSN 5930-01-212-0878



Rotary Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-01-212-0878 **Overall Length:** 5.062 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches single mounting facility **Individual Section Quantity:** 3 **Longest Horizontal Distance Between Mounting Centers:** 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.094 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and unthreaded hole single mounting facility **Contact Voltage Rating In Volts:** 600.0 dc at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility **Switch Actuator Indexing Position Quantity:** 10 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Terminal Type:** Wire lead **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Contact Load Current Rating:** 450.0 milliamperes resistive load dc at sea level and 350.0 milliamperes inductive load dc at sea level **Style Designator:**

Rectangular panel mount

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0